

FBZ


- Zero Scope-1 Emissions
- High Steam Quality
- Intuitive Touchscreen Control

1500 – 3000 kw

Electric Steam Boiler



Standard Features



FBZ boilers provide reliable, emissions-free operation for environmental sustainability. Equipped with industry-leading features as standard, FBZ boilers exceed expectations in large-scale electric applications.

ALL MODELS:

5,500 – 10,500 lb/hr Output F&A 212°F ASME Section I and IV Designs



*With appropriate fused disconnects installed upstream of unit


ADVANCED TOUCHSCREEN


- 5.7" Color Touchscreen
- Dedicated BMS Modbus
 - Other Integration
 Options Available
- Standard I/O
 - Dedicated Outputs for Element Staging
 - Individual Input Monitoring for Safety
 Devices with Alarm Annunciation



SPECIFICATIONS & DIMENSIONS

	MODEL	FBZ- 1500	FBZ-2000	FBZ-2500	FBZ-3000
SPECIFICATIONS					
Unit Size	kW	1,500	2,000	2,500	3,000
Steam Output	LBS/HR	5,250	7,000	8,750	10,500
Output	BTU/HR	511,8000	6,824,000	8,530,000	10,236,000
Water Capacity	GAL	1,026	1,026	1,320	1,320
ELECTRICAL (FLA)					
480/60/3	AMPS	1,814	2,418	3,023	3,627
600/60/3	AMPS	1,451	1,935	2,418	2,902
DIMENSIONS					
(A) Height w/o Trim	IN	91 1/4	91 1/4	91 1/4	91 1/4
(B) Width	IN	172 3/4	172 3/4	204 3/4	204 3/4
(C) Depth	IN	92 3/16	92-3/16	92 3/16	92 3/16
(D) Element Pull Clea	rance IN	53	53	53	53
WEIGHTS					
Shipping Weight	LBS	11,790	11,790	13,650	14,550
Operating Weight	LBS	18,020	18,020	20,195	22,680





NOTE: Specifications and dimensions are approximate and for reference only. Fulton practices continuous product improvement and reserves the right to change specifications and/or dimensions without notice.



972 Centerville Road Pulaski, NY 131<u>42</u>



fulton.com/fbz Drawings & documentation available online

FBZ-1500-3000_BROCHURE_240626

